

# Masaba Unloader

#### Load area

- Grate Heavy duty construction of 10' x 5' outside dimension
- **Construction** Heavy duty flat bar construction
- Self-Cleaning ramp Hinge on each side of grate
- Ramp bulkhead 10' wide by 9' long, folds for road transport Heavy duty hinge

#### Chassis

- **Frame** constructed of heavy duty steel tubing
- Tandem Axle Tandem walking beam with dual (8) 11 x 22.5R tires
- Landing jacks crank down landing jacks
- **Road portable package** Includes: 5<sup>th</sup> wheel hitch, brakes, lights, and mud flaps

#### **Discharge Conveyor**

- Size 48" BW
- Undercarriage Hydraulic raise and lower (maximum discharge height of 11')
- Frame Channel frame
- **Drive** Dual head drive
- Gear reducer Dual class II reducers with QD bushings
- Motors (2) 25 HP 1800 RPM
- **V- belt drive** -(2) with drive guard
- Capacity 1,000 STPH based on 100# per cu/ft of material, 1.5" minus
- Belt speed 225 FPM
- Flow control Adjustable slide gate
- **Discharge hood** with AR liner
- Loading area idlers CEMA C, Precision, 5" diameter flat carrier idlers
- Transition Idlers CEMA C, Precision, 20 degree, sealed, 5" diameter trough idlers
- Troughing idlers CEMA C, Precision, 35 degree, sealed, 5" diameter trough idlers, 3' spacing
- Return idlers CEMA C, Precision, 4" dia. rolls, rubber disc return, sealed, 10' spacing
- **Drive pulley** Heavy Duty, 20" diameter, drum pulley with Slide Lagging
- Tail pulley Heavy Duty, 14" diameter, self-cleaning wing pulley
- Snub pulley Heavy Duty, 14" diameter, drum pulley with 3/8" smooth rubber lagging
- Shafts C1045 turned and polished
- Bearings Pillow block bearings
- Take ups Screw type
- Belting 3-ply 3/16 x 1/16 330 PIW
- Belt splice Vulcanized
- Belt scraper Martin Pit Viper with twist tensioner

### **General Specifications**

- **Hydraulic pumping unit** 20 HP electric pumping unit with electric over manual controls for ramps and conveyor discharge
- **Electrical** 480 v/3 ph/60 hz enclosed panel. Includes main disconnect, circuit breaker and push button on/off switches with soft start. Mounted to chassis. With 100ft lead cord.
- **Remote control** Wireless remote
- **Guards** Tail pulley guard, v-belt guard and nip guard on head pulley. We do not warrant that our guards will meet all local codes. It is the responsibility of the end user to have them checked by a local inspector
- **Prime** (1) coat of 2-part urethane primer
- **Paint** (1) coat of 2 part urethane paint. Maroon with Yellow Guards
- **Owner's Manual** (1) copy for maintenance and parts

## **Purchase Price:**

### \$166,500.00

Unit is in stock (Item 16618), subject to prior sale. Terms are Net 10 Days after receipt of equipment, subject to prior credit approval. Sales tax is additional and charged at the appropriate rate. Freight is also additional and charged at our actual cost. Minimum rental period is two (2) months.

This equipment is rented without power source, power cable, safety stop switches, and other components that may be required, unless otherwise specified.

Unit has 70 hours of use



Ramps are folded up for shipment





