



924 Calle Negocio • Unit A
San Clemente, CA 92673
Phone: (949) 366-3070 • Fax: (949) 366-3069
www.aggregatemachineryspecialist.net

36" X 140' LOW PROFILE MAGNUM TELESCOPING STACKER

Conveyor Frame

- **Main Frame** – 52" Deep engineered truss 83' long
- **Counterweight** – On-board design installed in the main frame tail
- **Stinger Frame** – 36" Deep engineered truss 74' long
- **Stinger Drive** – **MASABA TRACK TECHNOLOGY**. Eliminates danger of cable breakage and uncontrolled roll back - No winch or cable. Conveyor extends to 140' length

Road Portability

- **Tubular Undercarriage** – Hydraulic raise & lower with 20 hp pumping unit
- **Swing Axle** – Road portable tandem walking beam axle with dual (8) 11R x 22.5 tires and wheels. Designed to be used in transport and radial travel mode.
- **Axle Jacks** – Jacks hydraulically lift conveyor to allow swing axle deployment
- **Power Travel** – Hydrashift, chainless power travel
- **Landing Legs** – Manual landing legs to ease loading/unloading of conveyor from truck.
- **Road Portable Package** – Including 5th wheel hitch, brakes, lights, and mud flaps
- **Towing Eye** – For pit transport
- **Anchor Pivot Plate** - Maintains tail end during radial travel
- **Tail Anchor Plate** – recommended for operating on non-concrete surfaces

Main & Stinger Components

- **Drives** – *Class II* head end
- **Motors** – 40 hp/30 hp (*dual 15 hp balanced drive*)
- **Gear Reducers** – Dodge TAI shaft mount with backstop
- **Capacity** – 1000 TPH based on 100# per cu/ft of material at 18 degrees
- **Belt Speed** – 400/600 FPM
- **Head Pulley** – Heavy Duty 16" diameter drum pulley with 3/8" herringbone lagging
- **Tail Pulley** – Heavy Duty 14" diameter self-cleaning wing type pulley
- **Take Ups** – Screw type
- **Belting** – 3-ply 3/16" x 1/16" 330 PIW
- **Belt Splice** – Flexco mechanical steel fasteners
- **Belt Scraper** – Martin Pit Viper with Twist Tensioner
- **Transition Idlers (main)** – CEMA C, PPI, 20 degree, sealed 5" diameter
- **Troughing Idlers** – CEMA C, PPI, 35 degree, sealed 5" diameter idlers, 4' spacing
- **Rubber Disc Return Idlers** – CEMA C, PPI, sealed 5" diameter return idlers, 10' spacing
- **Self-Aligning (main)** – (1) CEMA C, PPI, self-aligning idler
- **Hopper** – 6' long hopper with adjustable rubber flashing, radial receiving hopper and rock ledge

Controls

- **Complete Switchgear** - manual operation for extend/retract, raise/lower, axle jacks, start/stop conveyors and main disconnect
- **PLC** – Fully automated 4-program package with large color touch screen control
- **Material Flow Sensor** – pauses conveyor movement when material is not present

Gas Power Unit

- **13hp Electric Start Gas Power Unit with Hydraulics** - reservoir, filter, valve body and plumbing – allows user to operate axle jacks & extend stinger conveyor to remove weight from kingpin for easier removal from truck & operational set up

General Specifications

- **Guards** – Tail pulley guard, v-belt guard and nip guard on head pulley. We do not warrant that our guards will meet all local codes. It is the responsibility of the end user to have them checked by a local inspector
- **Steel Shot Blasted**
- **Prime** – (1) coat of 2 part urethane primer
- **Paint** – (1) coat of 2 part urethane paint. **METSO BEIGE with YELLOW GUARDS**
- **Owners Manual** – (2) copies for maintenance and parts

Included Options

- **Masaba FA** – folding axle
- **Remote grease bank** – for pulley bearings
- **Hydraulic landing legs** – for loading/unloading from truck, operated with 13 HP gas power unit or main electrical panel
- **Belt vulcanizing** – main conveyor & stinger conveyor belts
- **Dual power travel** – 4-wheel drive

PRICE:

\$239,910.00

Unit is in stock (Item 16600), subject to prior sale. Terms are Net 10 Days after receipt of equipment, subject to prior credit approval. Sales tax is additional and charged at the appropriate rate.

Pictures on following page.

