Kafka 9' x 16' Portable Grizzly Feeder
with 42" x 27' Incline Discharge Conveyor

- 5/16" plate 5/16" steel plate construction with tapered chute 3/8' plate on verticals
- I-beam construction on chassis
- 12" heavy channel frame on load reliever [bolt in]
- 10" heavy channel frame with cross bracing
- Precision CEMA C5" cans [all 20 degree rubber unequal idlers] 12" spacing
- Precision CEMA C5" returns 10' on center
- 18" lagged head pulley with 3-15/16" shaft 3-7/16"
- 18" wing tail pulley with 3 7/16" shaft
- 9" telescopic take-up unit
- Type E roller bearings
- 1045 shaft
- Dodge TA7315 40 to 1 gearbox
- 25 HP TEFC electric motor #102428
- 3 ply 330 3/16" top belting
- 2' high full length side boards
- Head & tail guarding – safety yellow
- Fifth wheel hitch
- Air brakes DOT tape
- Brake lights
- Tandem axle with hutch suspension on chassis
- Crank leveling legs in front-screw jack type and cribbing supports manual jacks included
- Primed and painted tan, safety yellow on guards
- Emergency Stop in the Electrical Panel
- Guarding on sides of conveyor
- Electric Hour Meter
- Flexco 42" EZP1 Belt Cleaner, installed
- 25 HP SC Variable Speed Drive, circuit breaker, control transformer, st/st buttons, speed pot, in NEMA 3R enclosure on free standing base
- Heavy-duty grizzly bar section 6" spacings round bar (hockey stick style) radio remote tipping grizzly 10 HP power unit EX remote, reversible
- Upper rock guard 1/8" steel plate both sides
- 16' square tubular frame with 1/4" plate steel side ramp headers, flip-up style each

- Return Nip Guards
- 2" galvanized walkway access with toe kick, 2" tubing uprights, 1-1/2", round pipe on top, angle iron midrail, all welded together

AMS Item 16678, subject to prior sale. Terms are Net 10 Days after receipt of equipment, subject to prior credit approval. Sales tax is additional and charged at the appropriate rate. Freight is also additional and charged at our actual cost.