



924 Calle Negocio • Unit A
San Clemente, CA 92673
Phone: (949) 366-3070 • Fax: (949) 366-3069
www.aggregatemachineryspecialist.net

KAFKA 9' x 16' Portable Grizzly Feeder with 42" x 27' Incline Discharge Conveyor

- 5/16" plate 5/16" steel plate construction with tapered chute 3/8" plate on
- verticals
- I-beam construction on chassis
- 12" heavy channel frame on load reliever [bolt in]
- 10" heavy channel frame with cross bracing
- Precision CEMA C5" cans [all 20 degree rubber unequal idlers] 12" spacing
- Precision CEMA C5" returns 10' on center
- 18" lagged head pulley with 3 15/16" shaft tdt 3 7/16"
- 18" wing tail pulley with 3 7/16" shaft
- 9" telescopic take-up unit
- Type E roller bearings
- 1045 shaft
- Dodge TA7315 40 to 1 gearbox
- 25 HP TEFC electric motor #102428
- 3 ply 330 3/16" top belting
- 2' high full length side boards
- Head & tail guarding – safety yellow
- Fifth wheel hitch
- Air brakes DOT tape
- Brake lights
- Tandem axle with hutch suspension on chassis
- Crank leveling legs in front-screw jack type and cribbing supports manual jacks
- included
- Primed and painted tan, safety yellow on guards

Included Options

- Emergency Stop in the Electrical Panel
- Guarding on sides of conveyor
- Electric Hour Meter
- Flexco 42" EZP1 Belt Cleaner, installed
- 25 HP AC Variable Speed Drive, circuit breaker, control transformer, st/st buttons, speed pot, in NEMA 3R enclosure on free standing base
- Heavy-duty grizzly bar section 6" spacings round bar (hockey stick style) radio remote tipping grizzly 10 HP power unit EX remote, reversible
- Upper rock guard 1/8" steel plate both sides
- 16' square tubular frame with 1/4" plate steel side ramp headers, flip-up style each
- Return Nip Guards
- 2" galvanized walkway access with toe kick, 2" tubing uprights, 1-1/2", round pipe on top, angle iron midrail, all welded together (per foot)
- AMS Item 16714