

P.O. Box 20340 Mesa, AZ 85277 Phone: (949) 366-3070

www.aggregatemachineryspecialist.net

Date: 6/22/23

AMS Transco 36" x 60' STACKABLE CONVEYORS

36" wide x 60' long Stackable Conveyor:

- Channel tube frame
- 20HP TEFC electric motor 3 Phase 480 Volts 60 Hz
- Dodge MTA shaft mount reducer with backstop
- 14" head pulley vulcanized rubber lagged with 2 15/16" 1045 shaft and Dodge bearings
- 12" tail pulley wing self-cleaning with 2 7/16" 1045 shaft and Dodge bearings
- Telescoping (tube in tube) screw type take-ups
- PPI Troughing rollers CEMA "C" 5" steel 20° close spacing loading zone
- PPI Troughing rollers CEMA "C" 5" steel 35° on 4' spacing
- PPI Return rollers CEMA "C" 5" flat steel on 10' spacing
- Skirted feed hopper 5' with ½" x 5 skirt board rubber adjustable clamps
- Belting 3ply 330PIW 3/16" top x 1/16" bottom covers vulcanized splice
- Primary belt scraper Flexco EZP-LS
- Standard head, tail, and nip guarding (additional guarding will be priced)
- Primer paint stone grey body with safety yellow guards
- Item #16734